



regulator plate

VABF-S4-2-R6C2-C-6

Part number: 546248

FESTO

For valve terminals VTSA and VTSA-F, standard port pattern to 15407-2, up to max. 6 bar.



Data sheet

| Feature | Value |
|-----------------------------------------|-----------------------------------------------------------------------------|
| Width | 18 mm |
| Based on the standard | ISO 15407-2 |
| Assembly position | Any |
| Controller function | Output pressure constant with secondary exhaust |
| Pressure gauge selection | possible |
| Pressure regulation range | 0.5 ... 6 bar |
| Inlet pressure 1 | 0.5 ... 10 bar |
| CE mark (see declaration of conformity) | to EU directive low-voltage devices |
| Operating medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Note on operating and pilot medium | Lubricated operation possible (subsequently required for further operation) |
| Corrosion resistance classification CRC | 0 - No corrosion stress |
| Protection class | IP65 NEMA 4 |
| Pilot medium | Compressed air in accordance with ISO8573-1:2010 [7:4:4] |
| Ambient temperature | -5 ... 50 °C |
| Product weight | 367 g |
| Pressure gauge connection | with retaining clamp |
| Material control panel | PA |
| Material regulator housing | Aluminium die cast |